

TITLE: MOTOR DATA. ISOLATING RANGE S2-15 MIN DUTY CYCLE, AC 3-380V/50Hz THREE PHASE
MODELS: CK, CKC

Actuator model	Output speed (rpm)	Max. tripping torque (N.m)	Nominal torque (N.m)	Motor speed (rpm)	Nominal Power (kW)	Nominal current (A)	Power at max tripping torque (kW)	Current at max tripping torque (A)	Locked rot. current (A)	Power factor (nominal) cos ϕ	Overcurrent prot. device setting (A)	Contacteur	Thyristor	
CK30	009	9	30	10	720	0,19	0,51	0,20	0,53	0,97	0,64	0,53	Standard	OPTIONAL
	012	12			720	0,19	0,51	0,23	0,60	1,21	0,65	0,60	Standard	OPTIONAL
	018	18			1440	0,19	0,49	0,26	0,68	1,82	0,56	0,68	Standard	OPTIONAL
	024	24			1440	0,23	0,61	0,28	0,75	2,13	0,62	0,75	Standard	OPTIONAL
	036	36			1440	0,28	0,73	0,32	0,84	2,82	0,39	0,84	Standard	OPTIONAL
	048	48			1440	0,27	0,70	0,38	1,00	2,83	0,50	1,00	Standard	OPTIONAL
	072	72			1440	0,27	0,72	0,41	1,08	3,55	0,53	1,08	Standard	OPTIONAL
	096	96			1440	0,30	0,79	0,59	1,56	3,67	0,42	1,56	Standard	OPTIONAL
	144	144			2880	0,36	0,95	0,79	2,08	6,12	0,55	2,08	Standard	OPTIONAL
	192	192			25	8,3	2880	0,59	1,54	0,83	2,19	6,31	0,87	2,19
CK60	009	9	60	20	720	0,34	0,89	0,37	0,96	5,88	0,49	0,96	Standard	OPTIONAL
	012	12			720	0,33	0,87	0,38	0,99	1,85	0,47	0,99	Standard	OPTIONAL
	018	18			1440	0,33	0,88	0,44	1,15	3,43	0,61	1,15	Standard	OPTIONAL
	024	24			1440	0,31	0,82	0,49	1,29	3,47	0,42	1,29	Standard	OPTIONAL
	036	36			1440	0,34	0,89	0,59	1,55	3,78	0,62	1,55	Standard	OPTIONAL
	048	48			1440	0,52	1,36	0,68	1,78	5,22	0,55	1,78	Standard	OPTIONAL
	072	72			1440	0,57	1,50	0,80	2,12	5,83	0,60	2,12	Standard	OPTIONAL
	096	96			1440	0,51	1,34	0,98	2,59	5,97	0,35	2,59	Standard	OPTIONAL
	144	144			2880	0,37	0,97	1,23	3,23	13,73	0,47	3,23	Standard	OPTIONAL
	192	192			50	16,7	2880	0,31	0,81	1,40	3,68	10,76	0,60	3,68
CK120	009	9	120	40	720	0,30	0,80	0,47	1,23	2,33	0,50	1,23	Standard	OPTIONAL
	012	12			720	0,32	0,83	0,48	1,27	2,30	0,54	1,27	Standard	OPTIONAL
	018	18			1440	0,46	1,20	0,63	1,67	7,10	0,53	1,67	Standard	OPTIONAL
	024	24			1440	0,46	1,20	0,73	1,93	4,77	0,59	1,93	Standard	OPTIONAL
	036	36			1440	0,53	1,40	1,00	2,63	7,30	0,62	2,63	Standard	OPTIONAL
	048	48			1440	0,63	1,67	0,99	2,60	9,83	0,61	2,60	Standard	OPTIONAL
	072	72			1440	0,92	2,43	1,38	3,63	13,07	0,64	3,63	Standard	OPTIONAL
	096	96			1440	0,95	2,50	1,62	4,27	15,57	0,51	4,27	Standard	OPTIONAL
	144	144			2880	1,10	2,90	2,22	5,83	20,33	0,85	5,83	Standard	OPTIONAL
	192	192			100	33,3	2880	0,90	2,37	2,25	5,93	20,50	0,69	5,93
CK250	009	9	250	83,3	720	0,73	1,93	0,86	2,27	6,30	0,45	2,27	Standard	OPTIONAL
	012	12			720	0,72	1,90	0,91	2,40	6,13	0,43	2,40	Standard	OPTIONAL
	018	18			1440	0,79	2,07	1,20	3,17	12,53	0,56	3,17	Standard	OPTIONAL
	024	24			1440	0,79	2,07	1,20	3,17	12,53	0,56	3,17	Standard	OPTIONAL
	036	36			1440	0,79	2,07	1,38	3,63	12,30	0,55	3,63	Standard	OPTIONAL
	048	48			1440	0,71	1,87	1,90	5,00	12,70	0,41	5,00	Standard	OPTIONAL
	072	72			1440	0,98	2,57	2,41	6,33	19,93	0,76	6,33	Standard	OPTIONAL
	096	96			1440	1,17	3,07	3,22	8,47	22,83	0,66	8,47	Standard	N/A
	144	144			2880	1,53	4,03	4,17	10,97	32,70	0,89	10,97	Standard	N/A
	192	192			200	66,7	2880	1,47	3,87	4,78	12,57	32,03	0,87	12,57
CK500	009	9	500	166,7	720	0,96	2,53	1,42	3,73	10,80	0,30	3,73	Standard	OPTIONAL
	012	12			720	1,34	3,53	1,77	4,67	10,90	0,24	4,67	Standard	OPTIONAL
	018	18			1440	0,77	2,03	1,85	4,87	13,03	0,57	4,87	Standard	OPTIONAL
	024	24			1440	0,79	2,07	1,90	5,00	15,57	0,65	5,00	Standard	OPTIONAL
	036	36			1440	1,01	2,67	2,43	6,40	21,37	0,63	6,40	Standard	OPTIONAL
	048	48			1440	1,48	3,90	3,05	8,03	27,40	0,58	8,03	Standard	OPTIONAL
	072	72			1440	1,74	4,57	4,13	10,87	30,80	0,71	10,87	Standard	OPTIONAL
	096	96			1440	2,12	5,57	5,66	14,90	52,77	0,65	14,90	Large	N/A
	144	144			2880	2,79	7,33	7,80	20,53	73,33	0,85	20,53	Large	N/A
	192	192			400	133,3	2880	2,46	6,47	7,59	19,97	69,57	0,83	19,97

Rotork Controls. All rights reserved. Subject to change without notice. Previous data sheets invalid with the issue of the latest data sheets. Due to production tolerance variation, the electrical values shown are averages compiled from Actuator production test data. Values are therefore provided for guidance only. Individual production tests are available on request (nominal load not included). Rotork Controls underwrite rated torque output only (specified tolerance -0/+10%)

AC 3-380V/50Hz asynchronous motors. Short-time duty S2 - 15 min, based on nominal torque at 40°C ambient temperature. Insulation class F. (H, under request). Motors are suitable for 60 starts/hour operation.

Motor data is approximate, due to manufacturing tolerances, there may be deviations from the stated values. Permissible variation of the mains voltage: $\pm 10\%$. Permissible variation of the mains frequency: $\pm 5\%$.

Electric motors are provided with thermoswitches to protect the motor windings against overheating. Thermoswitches are embedded in the motor windings: If those thermoswitches are not connected, or by-passed, in the control circuit actuators will NO longer comply with the essential safety requirements, in that case Rotork warranty will lapse. CKC electric actuators with centronik unit, see datasheet for centronik unit current consumption.